

Product Data Sheet
AGGREGATES

1. PRICE ADVANTAGE

ACT Recyclings Aggregates have a significant price advantage over the equivalent quarry products

2. ENVIRONMENTAL BENEFITS

By using recycled products such as aggregates (recycled concrete products) you are contributing to a more sustainable construction industry. Recycled concrete products have a carbon footprint 65% less than equivalent quarry products. In addition to this you are adding credibility to your project and complying with Green Star ratings.

COMMON APPLICATIONS

These products range from 5mm, 7mm, 10/14mm and 20mm and are suitable for drainage and filter applications, backfilling pipes and retaining walls or landscaping.

The concrete 30/60mm aggregate is commonly used for access tracks to sites, gabion fill and drainage.

COMPOSITION

Concrete or brick.

Test Method	Product Specification – AGGREGATES				
	Description	5mm	7mm	10/14mm	20mm
AS 1141.11.1	% passing 26.5mm sieve	-	-	-	100
	% passing 19.00mm sieve	-	-	100	90
	% passing 13.2mm sieve	-	-	85	17
	% passing 9.5mm sieve	100	100	14	2
	% passing 6.7mm sieve	100	61	1	1
	% passing 4.75mm sieve	71	4	1	-
	% passing 2.36mm sieve	2	2	-	-
	% passing 0.425mm sieve	2	1	-	-
	% passing 0.075mm sieve	1	-	-	-

All testing is performed by an independent NATA accredited laboratory and in accordance with Australian Standards.